

TECHNICAL DATA

SINGLE DIRECTION VIBRATORY PLATES

BP 25/50, BP 25/50 D



Maximum reliability

Engine and V-belts protected against damage



Powerful vibration

Plastic mat for paving work (optional)




Safe transport

Transport handles (standard) and transport wheels (optional)

Shipping dimensions in m3

BP 25/50 0,236
BP 25/50 D 0,245



Standard Equipment

- Vibration insulated steering bow, foldable
- Detachable steering handle
- Highly wear resistant base plate
- Fully automatic decompression (BP25/50D)
- Recoil starter
- Engine protection frame
- Single point lifting device
- Fully protected V-belt
- Carrying handles
- Protective covering
- 3-2-1 Warranty
- Automatic shutdown at low oil level (BP25/50)

Dimensions in mm

	H	H1	H2	L	L1	W
BP 25/50	658	962	700	1084	542	500
BP 25/50 D	708	962	700	1084	542	500

Technical Data

Weights

Operating weight CECE	kg	108	122
Basic weight	kg	107	123

Dimensions

Working width	mm	500	500
---------------------	----	-----	-----

Driving Characteristics

Working speed, max.	m/min	30	30
Max. gradeability (dep. on soil con.)	%	30	30

Drive

Engine manufacturer	Honda	Hatz
Type	GX 160	1B20
Emission stage	CARB Phase III	non EPA
Cooling	air	air
Number of cylinders	1	1
Performance ISO 3046	kW 3,6	3,1
Speed	min-1 3.600	3.000
Drive system	mech.	mech.
Fuel	gasoline	diesel
Fuel consump. aver. during operation	l/h 1,1	0,7

Exciter system

Frequency	Hz	92	92
Centrifugal force	kN	25	25
Amplitude	mm	1,11	1,11

Capacities

Fuel	l	3,1	3,0
Water	l	13,5	13,5

Technical modifications reserved. Machines may be shown with options.

Optional Equipment

- Sprinkler system (+10kg)
- Transport wheels (+4kg)
- Plastic mat
- Special painting
- Service Kit (BP25/50)
- TOUGH WARRANTY
- Comfort guide handle
- Central comfort guide handle (BP25/50)



PRE 230 17 010

130217 Sa01

BOMAG
 Hellerwald
 D-56154 Boppard
 P.O. Box 5162
 Tel. (0)6742 - 1000
 Fax (0)6742 - 3090

